



**STATE OF NEW YORK
DEPARTMENT OF TAXATION AND FINANCE
Office of Budget & Management Analysis
Bureau of Fiscal Services
Building 9, Room 234
W.A. Harriman Campus
Albany, NY 12227**

Patrick Ryan, Director
Budget & Accounting Services

Catherine Golden, Director
Procurement Services

January 14, 2014

**Amendment #2
For Invitation for Bids (IFB) 13-23 CONVENTIONAL CAB BOX TRUCK**

To All Potential Bidders:

The Department is issuing Amendment #2 as clarification for:

- Vehicle Specifications

All deletions are shown as shaded, strike-through text; all additions are made in red text.
All other requirements and conditions remain as indicated in the IFB.

VEHICLE SPECIFICATIONS:

Item

Class 7 truck with Box Body or Department approved equal.

Chassis-Cab

CAB-CHASSIS TRUCK (DRW), 4 x 2,
GVW 33,000#
220"cabaxle 286"wheelbase
12,000# F axle 21,000# R axle
ABS Brake System W/O Trailer Provisions
Conventional Regular Cab 106" BBC
Door Locks/Ign Switch Keyed with the same Keys
Base Vinyl Interior
Air conditioning
Basic Hi-Back Air Ride Seat
Back-Up Alarm 97 DB
Heated Side Mirrors
(2) 12 volt Accessory Outlets
Cruise Control
AM/FM Radio
Aluminum tool box 4ft x 3ft mounted behind cab
Daytime Running Lamps
Driver and Passenger side exterior grab handles
L.E.D Lighting throughout

Power Train

Diesel Fueled/Powered Engine
950 SQ IN Radiator
Lower Radiator Guard
Road Speed Gov set @ 72 MPH
Air Brakes
Aprox. 280HP @ 1600 rpm
3-12V 2100CCA Batteries
Auto transmission, 6F, 1R
Block Heater
2 - 50 Gal Alum Fuel Tanks
Fuel/Water Separator with thermostatic fuel temperature controlled electric heater, Water in fuel sensor
Transmission – Mfr.& Mdl : Allison, 3500 RDS
Extended Powertrain Warranty – Longest Terms Available

Body

97"IH 97"TW 25' 10 7/8" IL
26' 5 5/8" OL 103 3/8" OH 102" OW
1-3/8" Laminated Hardwood Floor with 1/8" Diamond Plate Steel over entire floor.
Plywood Lined Sides and front walls
1/8" Diamond Plate reinforcement over plywood on sides and front walls 4' up from floor
E Track on side and front wall's 24" and 48"
Include additional cargo light
Rear bumper under carriage protection
Rubber dock bumpers 2 ea.
~~4" riser in place of standard 1 1/2" riser~~ **Standard 1 1/2" Riser is required**
~~Minimum 2,000# Tuck Away Lift Gate Aluminum~~
HLF Heavy Duty, Level Ride Flipaway Gate 2,500 lb. capacity OR Equal Lift Gate
Roll-up Door